

ELECTRONIC HOOTER (MODEL EH)

SMART ELECTRONIC HOOTER is a solid-State Electronic Hooter of 100 Watt with 6 different siren Tone of 1 min with Sound output is 140 dB@ 1 meter @ 100W. An Internal Volume control Pot is provided for output volume control, **2 external loud speaker horns of 8 ohms 60 Watt are connected with the unit.**

The MAIN CONTROL CARD with power transformer is fitted in a wall mountable type IP 55/65 grade ABS body housing of Grey color, weighing about 850gms, Works on 220/110 V AC.

SMART FEARUTES: -

- Operating on 220/110 V AC
- Six Different Tone for 1 min.
- Sound output is 140 dB @ 1 meter @ 100W.
- Internal Volume control Pot & 2 external loud speaker horns of 8 ohms 60
- ABS body with IP 55/65 grade
- Customized Activation

TECHNICAL SPECIFICATIONS: -

ELECTRICAL: -

Tone frequency range Power Source Power consumption Stand by consumption Power output Sound output

ENVIRONMENTAL: -

Temperature Humidity Enclosure **MECHANICAL: -**Body

Dimensions Net weight kgs Standard mounting 300Hz to 1000Hz 220/110 V AC (PREDEFINED) < 100 Watt. < 2 Watt. 100 Watt (RMS) 140 dB @ 1 meter @ 100W.

0 to +60 C. 0 to 95% Rh non-condensing. Dustproof fully gasketted.

ABS.

170 x 125 x 90 mm. .850 kg. Vertical wall.

INDUSTRIAL AUTOMATION SIMPLIFIED.

cables & wireless co.

FF 75 RAJAT ARCADE, MIDC T-POINT, AMRAWATI ROAD, WADI, NAGPUR -440023.MAHARASHTRA, INDIA. PHONE:- +917104-224381 Fax:- +917104-224381. Cell: - +9198226 95746, +919822941190. Website:

"(Specifications and description subjected to change without prior notice)"

