

SMART INDUSTRIAL HOTLINE SYSTEM



SMART HOTLINE TELEPHONE SYSTEM has two desktop phones connected by single pair wire with one **SMART CONTROLLER UNIT** (3" X 10.5" X 4.5"), the controller is AC powered (220 V AC). It can be placed at any location (near to any of the two phones or in center). When one phone goes off hook second phone will get ring tone. It will keep ringing till it is picked up. The system will operate vice versa for second unit. Any of the two on hook phone will keep on ringing till the other off hook phone goes on hook.

- 1) Connect link of the phone 1 to the CONTROLLER UNIT.
- 2) Connect link of the phone 2 to the CONTROLLER UNIT.
- 3) Connect 220 VAC mains input to the CONTROLLER unit.
- 4) Switch on the supply to the unit.
- 5) System has got continuous online UPS backup for power Failure

OPERATIONS: -

OUT GOING CALLS:-

- 1) Lifting the receiver of any phone will activate the ringer of other phone.
- 2) Replacing the receiver on cradle disconnects the call.
- 3) On pick up by other party the communication is in private mode.

INCOMING CALLS:-

- 1) The ringer energized after the handset of any phone is lifted and the ringer will be heard.
- 2) To communicate lift the handset and talk.
- 3) In case nobody picks up the phone and caller party disconnects the call, the phone will get disconnected automatically.

INDUSTRIAL COMMUNICATIONS SIMPLIFIED .

cables & wireless co.

FF 75 RAJAT ARCADE, MIDC T-POINT,
AMRAWATI ROAD, WADI, NAGPUR -440023.
PHONE:-07104-321913,07104-224381.

Fax:- 07104-224381.

Cell: - 098226 95746, 09225227945, 09822941190.

Website:- www.cnwcom.in. E-mail: - cnwcom@gmail.com.

"(Specifications and description subjected to change without prior notice)"