

SMART LOUDRINGER. MODEL LR-III

SMART LOUDRINGER can be connected with **SMART INDUSTRIAL TELEPHONES** or with TEL line of any EPABX system, it has an integrated annunciation system & can be connected directly to TEL line or in parallel with any TEL unit . Very useful in heavy, medium and small process industries.

When a call is made to the telephone, the external loud ringer activates and the ringing is heard over the loudspeaker horn.



CONNECTIONS: -

- 1) Connect the external loud ringer using single pair cable from the Industrial Telephone/ TEL LINE from EPABX SYSTEM/ in parallel with any make TEL UNIT.
- 2) Connect the power supply 220 VAC/ 110 VAC (selectable).

TECHNICAL SPECIFICATIONS: -

ELECTRICAL PERFORMANCE: -

Audible range frequency response 300 - 3400 Hz.
Ringer output max 107 db.

ELECTRICAL REQUIREMENTS: -

Connection method PCB terminal block type.
Fuse 0.25 Amp 2AG fast blows.
Power supply 220 VAC / 110 VAC switch able.

ENVIRONMENTAL: -

Temperature 0 to +60 C.
Humidity 0 to 95% Rh non-condensing.
Enclosure Dustproof fully gasketed.

MECHANICAL: -

Body 16 SWG steel.
Surface finish Powder coated.
Dimensions 240 x 170 x 250 mm.
Net weight kgs 3 kg.
Standard mounting Vertical wall.

CONFIRMING TO IP 65-DEGREE PROTECTION.

INDUSTRIAL COMMUNICATIONS SIMPLIFIED .

Cables & Wireless Co.

FF 75 RAJAT ARCADE, MIDC T-POINT,
AMRAWATI ROAD, WADI, NAGPUR -440023.
PHONE:-07104-321913,07104-224381.

Fax:- 07104-224381.

Cell: - 098226 95746, 09225227945, 09822941190.

Website:- www.cnwcom.in. E-mail: - cnwcom@gmail.com.

"(Specifications and description subjected to change without prior notice)"