

SMART LOUDSPEAKER HORN. (MODEL LSOD)

SMART LOUDSPEAKER HORNS:-

Outdoor loudspeakers are of 60 watts (RMS). Loud speakers are connected to PA TELEPHONE /PAGE PRIVATE UNITS; up to two loud speakers can be connected to each UNIT. For more number of loudspeakers in each location **SMART EXTERNAL AMPLIFIERS** can be connected to PA TELEPHONE/PAGE PRIVATE UNITS.



TECHNICAL SPECIFICATIONS: -

ELECTRICAL PERFORMANCE: -

Audible range frequency response 300 - 3400 Hz.
Loudspeaker horn output max 107 dB.

ELECTRICAL SPECIFICATIONS: -

Coil resistance. 6 Ohm.
Coil impedance@ 1 Khz 8 Ohm.
Rated output watt RMS 60 Watts.
Sound level@ 30 watt RMS 70 dB.

ENVIRONMENTAL: -

Temperature 0 to +60 C.
Humidity 0 to 95% Rh non-condensing.
Enclosure Dustproof fully gasketted.

MECHANICAL: -

Body ABS.
Dimensions 240 x 170 x 250 mm.
Net weight kgs .8 KGS.
Standard mounting 'C" Clamp Type.

CONFIRMING TO IP 65-DEGREE PROTECTION.

INDUSTRIAL COMMUNICATIONS SIMPLIFIED .

cables & wireless co.

FF 75 RAJAT ARCADE, MIDC T-POINT,
AMRAWATI ROAD, WADI, NAGPUR -440023.
PHONE:-07104-321913,07104-224381. Fax:-07104 -224381.
Cell: - 098226 95746, 09225227945, 09822941190.
Website:- www.cnwcom.in. E-mail: - cnwcom@gmail.com.

"(Specifications and description subjected to change without prior notice)"