

SMART PAGE PRIVATE TELEPHONE INTERFACE UNIT

SMART TELEPHONE INTERFACE UNIT is an integrated system used for patching of PLANT EPABX SYSTEM to **SMART PAGE/PRIVATE PHONE SYSTEM**.

One has to just lift the telephone handset of any extension of PLANT EPABX, dial the extension number of the UNIT and after the call matures automatically, make necessary announcement. The communication between the calling party and the called party is in private mode, when the called party lifts the handset and presses the **PAGE CANCEL BUTTON**.

SMART TELEPHONE INTERFACE UNIT disconnects automatically if the calling party disconnects the call. The announcement is made at ALL THE location over the plant.

SPECIFICATIONS: -

Electrical Requirement :-

Power Source:	220 volts / 110 volts AC (SWITCH ABLE).
Phone line:	24 VOLTS (EPABX) / 50 VOLTS (TEL LINE).
Power consumption:	< 5 Watts.
Insulation:	600 v for 3 min between power source & Telephone line.

Mechanical Specifications :-

Weight:	1.2Kgs.
Construction:	16 gauge Powder Coated Steel Body.
Standard mounting:	Desktop type/Panel type.

Environmental :-

Moisture Resistance:	0 to 95% humidity with PCB conformal coated.
Temperature Range:	0 to +60 C.
Dust resistance:	Fully weather proof enclosure.

INDUSTRIAL COMMUNICATIONS SIMPLIFIED .

cables & wireless co.

FF 75 RAJAT ARCADE, MIDC T-POINT,
AMRAWATI ROAD, WADI,
NAGPUR -440023
PHONE:-07104-321913,07104-224381 Fax:- 07104-224381.
Website:- www.cnwcom.in E-mail: - cnwcom@gmail.com.
Cell: - 098226 95746, 09225227945, 09822941190.

“(Specifications and description subjected to change without prior notice)”