

# SMART OPERATOR CONSOLE (PAGE PRIVATE) MODEL DTSM-I

**SMART OPERATOR CONSOLE** is designed to be used with **SMART PAGE/PRIVATE SYSTEM**

It provides paging capability a very important plant communication function in one durable, easy-to-operate package. Through the page function individuals can be contacted anywhere in the plant from the control room. It has got integrated amplifier on a Single PCB for driving the internal speakers. It is connected in parallel loop with 3 core signal cable from **SMART PAGE/PRIVATE SYSTEM**.

Operation is simple: the user PRESSES the connect button, the set goes to paging mode. Speaking directly into the MIC, the user announces his page. The responding individual can communicate by lifting the handset (HANDSET TYPE)/by pressing the CONNECT BUTTON (VANDAL RESISTANT TYPE) and presses a PAGE CANCEL BUTTON to cancel the ongoing paging on other stations



## SPECIFICATIONS: -

### Electrical Requirement: -

Power Source	220 VAC / 110 V AC (SWITCH ABLE).
Power consumption	< 15 Watts.
Stand by consumption	< 1 Watts.
Amplifier	10 Watts (RMS).
Internal Speaker	3 Watts, 8 Ohms.
External Box Speaker (optional)	10 Watts, 8 Ohms.
Insulation	600 v for 3 min between power source & Parallel line.

### Mechanical Specifications: -

Weight	.600 Kgs.
Construction	16 gauge Powder Coated Steel Body.
Standard mounting	Desk top.
Microphone	Noise canceling dynamic.

### Environmental: -

Moisture Resistance	0 to 95% humidity with PCB conformal coated.
Temperature Range	0 to +60C.
Dust resistance	Fully weatherproof enclosure.

**INDUSTRIAL COMMUNICATIONS SIMPLIFIED .**

*cables & wireless co.*

FF 75 RAJAT ARCADE, MIDC T-POINT,  
AMRAWATI ROAD, WADI,  
NAGPUR -440023.

PHONE:-07104-321913,07104-224381.FAX:- 07104-224381.

Website:- www.cnwcom.in. E-mail: - cnwcom@gmail.com.

Cell: - 098226 95746, 09225227945, 09822941190.

"(Specifications and description subjected to change without prior notice)"